


TECHNICAL DATA

SINGLE DRUM ROLLERS

BW 226 DH-5, BW 226 PDH-5





Dimensions in inch

	A	B	D	H	H2	K	L	O1	O2	S	W
BW 226 DH-5	132.3	98.4	63.0	92.5	121.3	16.9	265.4	7.3	7.3	1.57	83.9
BW 226 PDH-5	132.3	98.4	59.1	92.1	121.3	16.9	265.4	7.3	7.3	1.38	83.9

Shipping dimensions in cub.yd

BW 226 DH-5
BW 226 PDH-5

without ROPS

51,768
51,544

with ROPS

67,886
67,886

Machine type	Compaction output (cub.yd/h)			
	Rock fill	Gravel, sand	Mixed soil	Silt, clay
BW 226 DH-5	1543.4-2772.8	1151.0-2288.9	889.4-1569.5	457.8-915.6
BW 226 PDH-5	1543.4-2772.8	1151.0-2288.9	889.4-1569.5	497.0-954.8

Machine type	Compacted layer thickness (in)			
	Rock fill	Gravel, sand	Mixed soil	Silt, clay
BW 226 DH-5	78.7	59.1	39.4	19.7
BW 226 PDH-5	78.7	59.1	39.4	21.7

Technical Data

BOMAG BW 226 DH-5

BOMAG BW 226 PDH-5

Weights

Grossweight	lb	58,886	60,627
Operating weight CECE w. ROPS-cabin	lb	55,116	56,747
Axle load, drum CECE	lb	37,633	39,242
Axle load, wheels CECE	lb	17,483	17,505
Static linear load CECE	lb/in	448.8	

Dimensions

Working width	in	83.9	83.9
Track radius, inner	in	167.7	167.7

Driving Characteristics

Speed	mph	0- 6.2	0- 5.6
Max. gradeability without/with vibr.	%	50/47	52/49

Drive

Engine manufacturer		Deutz	Deutz
Type		TCD 6.1 L6	TCD 6.1 L6
Emission stage		Stage V / TIER4f	Stage V / TIER4f
Exhaust gas aftertreatment		DOC+DPF+SCR	DOC+DPF+SCR
Cooling		Liquid	Liquid
Number of cylinders		6	6
Performance ISO 3046	hp	201.2	201.2
Performance SAE J 1995	hp	202.0	201.0
Speed	rpm	2,300	2,300
Fuel		Diesel	Diesel
Electric equipment	V	12	12
Drive system		hydrost.	hydrost.
Drum driven		standard	standard

Drums and Tires

Number of pad feet			150
Area of one pad foot	s1.in		21.2
Height of pad feet	in		3.9
Tire size		23.5-25 16PR	750/65 R26

Brakes

Service brake		hydrost.	hydrost.
Parking brake		hydromec.	hydromec.

Steering

Steering system		oscil.artic.	oscil.artic.
Steering method		hydrost.	hydrost.
Steering / oscillating angle +/-	deg	35/12.0	35/12.0

Exciter system

Drive system		hydrost.	hydrost.
Frequency	vpm	1,560.0/1,560.0	1,560.0/1,560.0
Amplitude	in	0.083/0.047	0.067/0.035
Centrifugal force	lb	73,737/42,039	73,737/39,342
Centrifugal force	t	7,531/4,294	7,531/4,024

Capacities

Fuel	gal	74.0	74.0
------------	-----	------	------

Technical modifications reserved. Machines may be shown with options.

Standard Equipment

- ☒ BOMAG ECOMODE
- ☒ Double pump system for travel drive
- ☒ Self locking differential
- ☒ Rear axle with twin spring accumulator brakes
- ☒ Hydrostatic travel and vibration drive
- ☒ Hydrostatic articulated steering
- ☒ Articulated joint lock
- ☒ Seat with arm rest and adj. for position and height
- ☒ Battery disconnect switch
- ☒ Single lever control for travel and vibration
- ☒ Warning, information and operation displays with LCD
- ☒ Loading mode
- ☒ Emergency STOP
- ☒ Working lights front / rear
- ☒ Back-up alarm
- ☒ 2 Scrapers
- ☒ Warning horn
- ☒ Tractor tires (PDH)

Optional Equipment

- ☐ * ROPS/FOPS cabin with seat belts
 - Sliding window
- ☐ Rearview camera
- ☐ Air condition
- ☐ Radio (Bluetooth)
- ☐ Pre start cabin heating
- ☐ Comfort package: Adjustable seat and adjustable steering column
- ☐ Rotary beacon
- ☐ Indicator and hazard lights
- ☐ BOMAG ECOSTOP
- ☐ ECONOMIZER
- ☐ TERRAMETER
- ☐ BOMAG TELEMATIC POWER
- ☐ Special painting
- ☐ Padfoot segment kit (DH)
- ☐ Environmentally compliant hydraulic oil
- ☐ Measuring- and machine data interface for third-party suppliers
- ☐ Reversing alarm buzzer with broad band audio
- ☐ LED Working lights (Cabin)
- ☐ Highly wear resistant drum (DH)
- ☐ Rock tire

* Standard delivery with CE conformity
(valid within European Union)

